

ENDURA

ENDURA 3.5-25x56 FFP

Features

- Unrestricted zero-stop elevation turret with revolution indicator (100MOA or 32.0MRAD travel range)
- Expansive zoom erector configuration with versatile 3.5-25 magnification range
- Robust 34mm tube design of single piece construction
- Fully multi coated lenses (Low Dispersion)
- Choice of M4PD (MOA), or B2GD (MRAD) glass etched reticle installed in the first focal plane (FFP)
- 0.25MOA or 0.1MRAD adjustment per click
- Includes a throw lever for magnification ring
- Includes sunshade and flip up covers
- Includes turret driver tool and lens cloth
- Nitrogen Purged, waterproof, fogproof, shockproof
- Each unit is hand tested in the United Kingdom before sale

Warranty

- Repair or Replace if the scope doesn't perform. **No charge. No time limit.**

Specification

MAGNIFICATION RANGE	3.5-25x
FIELD OF VIEW @ 100M	9.05m - 1.46m
EYE RELIEF	100mm - 90mm
MAX ELEVATION ADJUSTMENT RANGE	>100.0MOA or 32.0MRAD
MAX ELEVATION ADJUSTMENT RANGE w ZERO STOP	Unrestricted >100.0MOA or 32.0MRAD
ADJUSTMENT VALUE PER CLICK	0.25MOA or 0.1MRAD
ADJUSTMENT PER TURN	25.0MOA or 10.0MRAD
MINIMUM PARALLAX DISTANCE AT FULL POWER	13.7m
RETICLE CHOICES	M4PD (MOA) or B2GD (MRAD)
RETICLE INSTALL	First Focal
TOTAL LENGTH	375mm
WEIGHT	995g
TUBE DIAMETER	34mm
CONSTRUCTION	1 Piece Tube/Saddle
OBJECTIVE LENS DIAMETER	56mm
OUTER OBJECTIVE DIAMETER	64.5mm
OUTER OCULAR DIAMETER	44mm
ADDITIONAL SUNSHADES	1 Supplied
FLIP UP LENS COVERS	Yes, Supplied
CONFIGURATIONS AND ORDER CODES	B251 (MOA) OR B252 (MRAD)

